

Diphy

2016

Mirco Crosatto

Diphy is a collection of luminous and transparent petals, combining natural aesthetics with a technological soul. The central source transmits light to the curving edges whilst the micro-incisions of the surfaces create soft and uniform ambient lighting. OptiLight™ technology allows Diphy to disappear from view when switched off, only to magically reappear when switched on.

• **Thermocurved PMMA diffuser, central body and mounting in aluminium. Finish: white/transparent.**

Diphy è una collezione di petali luminosi e trasparenti, che combina l'estetica organica a un'anima tecnologica. La sorgente centrale trasmette la luce ai bordi sinuosi e alle microincisioni delle superfici, creando un'illuminazione d'ambiente morbida e omogenea. La tecnologia OptiLight™ permette a Diphy di scomparire alla vista se spenta, per riapparire magicamente quando accesa.

• **Diffusore in PMMA termocurvato, corpo centrale e montatura in alluminio. Finitura: bianco/trasparente.**

Diphy ist eine Kollektion an transparenten, leuchtenden Blütenblättern, welche die organische Ästhetik mit einer technologischen Seele kombiniert. Die zentrale Lichtquelle sendet das Licht zu den kurvenförmigen Rändern und den Mikrogravuren der Oberfläche und schafft so ein weiches und homogenes Umgebungslicht. Die OptiLight™-Technik erlaubt Diphy aus dem Sichtfeld zu verschwinden, sobald sie abgeschaltet ist, um magischerweiser wieder zu erscheinen, sobald sie eingeschaltet wird.

• **Diffusor aus heißgebogenem PMMA, Mittelkörper und Gestell aus Aluminium. Ausführung: weiß/transparent.**






WALL/CEILING **DIPHY**




STILNOVO 2023/24



1. Diphy L54




Dimming kits




-  **KIT0079** / CASAMBI
DALI / 1 art / in
-  **KIT0080** / CASAMBI
PH-CUT / 1-2 art / in
-  **KIT0026**
PH-CUT / 1-4 art



2. Diphy L76



Dimming kits

-  **KIT0079** / CASAMBI
DALI / 1 art / in
-  **KIT0080** / CASAMBI
PH-CUT / 1 art / in
-  **KIT0026**
PH-CUT / 1-2 art

MOD	CODE	FINISH	SOURCE	INPUT	DIMMING	CCT (K)	LUMEN	CRI	IP	OPTICS
1	8163	WH TR	TopLED 21W	220-240V	DALI Push	3000	2609	90	20	Diffused
	8163M	WH TR	TopLED 21W	220-240V	DALI Push	2700	2426	90	20	Diffused
	8166	WH TR	TopLED 21W	220-240V	Phase-cut	3000	2609	90	20	Diffused
	8166M	WH TR	TopLED 21W	220-240V	Phase-cut	2700	2426	90	20	Diffused
2	8164	WH TR	TopLED 40W	220-240V	DALI Push	3000	4370	90	20	Diffused
	8164M	WH TR	TopLED 40W	220-240V	DALI Push	2700	4064	90	20	Diffused
	8167	WH TR	TopLED 40W	220-240V	Phase-cut	3000	4370	90	20	Diffused
	8167M	WH TR	TopLED 40W	220-240V	Phase-cut	2700	4064	90	20	Diffused

Other versions: floor, p. 98; suspension, p. 164.